

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number
WO 2004/039927 A1

(51) International Patent Classification⁷: C10L 9/02, 9/08

(74) Agent: FREEHILLS CARTER SMITH BEADLE; Level 32, MLC Centre, 19-29 Martin Place, Sydney, New South Wales 2000 (AU).

(21) International Application Number:

PCT/AU2003/001409

(22) International Filing Date: 23 October 2003 (23.10.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2002952315 29 October 2002 (29.10.2002) AU
2002952446 1 November 2002 (01.11.2002) AU


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): UCC ENERGY PTY LIMITED [AU/AU]; 213 Miller Street, North Sydney, New South Wales 2060 (AU).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 2004/039927 A1

(54) Title: PROCESS FOR DEMINERALISING COAL

(57) Abstract: A process for demineralizing coal includes the steps of forming a slurry of coal particles in an alkali solution, the slurry containing 10-30 % by weight coal, maintaining the slurry at a temperature of 150-250 °C under a pressure sufficient to prevent boiling, separating the slurry into an alkalinized coal and a spent alkali leachant, forming an acidified slurry of the alkalinized coal, the acidified slurry having a pH of 0.5-1.5, separating the acidified slurry into a coal-containing fraction and a substantially liquid fraction, subjecting the coal-containing fraction to a washing step, particularly a hydrothermal washing step, in which the coal-containing fraction is mixed with water and a polar organic solvent or water and an organic acid to form a mixture and separating the coal from the mixture. The demineralized coal has an ash content of from 0.01-0.2 % by weight and can be used a feed to a gas turbine.